



Digivisual Technologies Inc.


PLUG TO VIEW IP Pen Tilt Camera

Model: DV-PTIPN802F

Features

- PT: PT control, can cover wider areas
- Plug and View : User zero Configuration. By leading peer-to-peer client software with the cloud P2P server, plug and view
- Remote Viewing: Use P2P APP, users can remote view
- Motion detection and alarm: Support motion detection send alarm information by e-mail, FTP
- Night Vision: 24-hour surveillance
- WI-FI Connect: WI-FI easily connect to a wireless router

Specification

| | | | |
|---|-------------------------------|-----------------------|--|
| <p style="text-align: center;">PICTURE</p>  | Hardware Features | Interface | One 10/100Mbps RJ45 WI-FI Support Power Interface Reset Button Built-in Microphone 3.5mm Audio Out Interface 11 infrared LED, up to 10m distance |
| | | Pan/Tilt | Horizontal:355° Vertical: 120° |
| | | Image Sensor | 1/4" CMOS Sensor |
| | | Display Resolution | 720P(1280*720)/VGA(640*480)/QVGA(320*240) |
| | | Lens | f=3.6mm,F=2.0 |
| | | Dimension | 120*103*130mm |
| | | Power Input | 5V DC, <6W |
| | Wireless Features | Wireless Speed | IEEE802.11b/g/n |
| | | Operating Frequency | 2.4 GHz |
| | Software Features | Protocols & Standards | TCP/IP, DHCP, ARP, ICMP, FTP, SMTP DDNS, NTP, UPnP, HTTP, TCP,UDP/IP,P2P |
| | | Security | WPA/WPA2-PSK,WPA-/WPA2-AES,WEP |
| | | Maximal Frame Rate | 30fps |
| | | Code rate | 16kbps ~ 4Mbps |
| | | Account permissions | Three Level |
| | | Motion Detection | Support F motion detection |
| | | Manage Software | Setup Wizard, P2P View client software (support Android, Windows), IP / DDNS View client software (support Android), PC centralized control and management platform |
| | | Audio | Two-way audio |
| | | PC Requirements | CPU 2.0GHz or above (suggested 3.0GHz) Memory Size 256MB or above (suggested 1.0GHz) Display Card 64M or above Windows 7,Vista,XP,Mac OS Browser:IE6/IE7/IE8/IE9,Firefox,Safari,Goolge Chrome, other standard browsers |
| | | Other | Package Contents |
| | Temperature | | Operate Temper: -10°C ~ 50°C |
| Humidity | Operating Humidity: 10% ~ 80% | | |

Tel: 416-292-4898 Fax: 416-292-6660

Address: 110 Silver Star Blvd. Unit 102, Toronto, Ontario, M1V 5A2, Canada

Email: sales@digivisual.ca

Web Site: www.digivisual.ca